

533,005



PCT

[CA/CA]; 6100, chemin Deacon, apt. 10P, Montreal Québec H3S 2V6 (CA). **OBEID, Victor** [US/US]; 1517 Green Valley Drive, Collegeville, PA 19426 (US).

(74) Agents: PRINCE, Gaétan et al.; Brouillette Kosie Prince, 1100 René-Lévesque Blvd. West, 25th Floor, Montréal, Québec H3B 5C9 (CA).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(72) Inventors; and

(75) **Inventors/Applicants (for US only):** **CARRIER, Michel** [CA/CA]; 6161 Rodolphe-Mathieu, Montréal, Québec H1M 3H9 (CA). **GARON, André** [CA/CA]; 7501 Joseph-Renaud, apt. 302, Ville d'Anjou, Québec H1K 3V7 (CA). **CAMARERO, Ricardo** [CA/CA]; 100 Berlioz, Verdun, Québec H3E 1N4 (CA). **PELLETIER, Conrad**

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(57) Abstract: The blood pump comprises a stationary housing structure and a rotative impeller mounted within the stationary housing structure and defining with the stationary housing structure passages through which blood pumped by the rotative impeller flows through the pump. An inflow bearing comprises an inflow frusto-conical face of the rotative impeller and an inflow frusto-conical bushing of the stationary housing structure having an inner face. Similarly, an outflow bearing comprises an outflow frusto-conical face of the rotative impeller and an outflow frusto-conical bushing of the stationary housing structure having an inner face. The inner face of both the inflow and outflow frusto-conical bushings (a) comprises at least three axial grooves evenly spread out around a longitudinal axis of the blood pump, and (b) successively defines a taper and a land in the direction of rotation of the rotative impeller between each pair of successive grooves. The taper has a diameter that gradually decreases in the direction of rotation of the rotative impeller, while the land has a generally constant diameter to form a seat for the frusto-conical face of the rotative impeller.

WO 2004/101029 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*